



Revision Date: 14-Apr-2025

Safety Data Sheet

Spartan Chemical Company, Inc.

1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Product Name: XTRACTION II
Product Code: 3096 , 3096R
Recommended Use: Carpet cleaner
Uses Advised Against: For Industrial and Institutional Use Only

Manufacturer/Supplier: Spartan Chemical Company, Inc.
1110 Spartan Drive
Maumee, Ohio 43537 USA
800-537-8990 (Business hours)
www.spartanchemical.com

24 Hour Emergency Phone

Numbers:
Medical Emergency/Information: 888-314-6171
Transportation/Spill/Leak: CHEMTREC 800-424-9300

2. HAZARDS IDENTIFICATION

GHS Classification

Skin corrosion/irritation: Category 1 Sub-category C
Serious eye damage/eye irritation: Category 1

Label elements

Signal word:

Symbols:

Danger



Hazard statements: Causes severe skin burns and eye damage

Precautionary Statements - Prevention:

Do not breathe dust/fume/gas/mist/vapors/spray
Wash face, hands and any exposed skin thoroughly after handling
Wear protective gloves/clothing and eye/face protection
Immediately call a POISON CENTER or doctor

Precautionary Statements - Response:

Eyes:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Skin:

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. Wash contaminated clothing before reuse.

Inhalation:

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Ingestion:

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

-Specific Treatment:

See Safety Data Sheet Section 4: "FIRST AID MEASURES" for additional information.

Precautionary Statements - Storage: Store locked up.

Precautionary Statements - Disposal: Dispose of contents and container in accordance with local, state and federal regulations.

Hazards not otherwise classified (HNOC): Not applicable

Other hazards:

- May be harmful if swallowed
- Inhalation of vapors or mist may cause respiratory irritation.
- Keep out of reach of children

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical name	CAS No.	Weight-%
Water	7732-18-5	80-100
C9-11 Alcohols Ethoxylated	68439-46-3	1-5
Sodium Carbonate	497-19-8	1-5
Butoxyethanol	111-76-2	1-5
Tetrasodium EDTA	64-02-8	1-5
Sodium Naphthalene Sulfonate, Sodium Salt	111163-74-7	1-5
Hydrochloric Acid	7647-01-0	<0.1
Benzyl Benzoate	120-51-4	<0.1
Acid Green 25	4403-90-1	<0.1
Acid Yellow 36	587-98-4	<0.1
Fragrance	PROPRIETARY	<0.1

Specific chemical identity and/or exact percentage of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Eye contact: Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN.

Skin contact: Take off immediately all contaminated clothing and shoes. Rinse with water or shower for at least 15 minutes. IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN. Wash contaminated clothing before reuse. Discard or destroy contaminated shoes.

Inhalation: Remove victim to fresh air and keep at rest in a position comfortable for breathing. IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN.

Ingestion: Rinse mouth. Do NOT induce vomiting. IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN. Never give anything by mouth to an unconscious person.

Note to physicians: NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media: Product does not support combustion. Use extinguishing agent suitable for type of surrounding fire.

Specific Hazards Arising from the Chemical: Dried product is capable of burning. Combustion products are toxic.

Hazardous Combustion Products: May include Carbon monoxide Carbon dioxide and other toxic gases or vapors.

Protective Equipment and Precautions for Firefighters: Wear MSHA/NIOSH approved self-contained breathing apparatus (SCBA) and full protective gear. Cool fire-exposed containers with water spray.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Avoid contact with skin, eyes or clothing. Use personal protective equipment as required.

Environmental Precautions: Do not rinse spill onto the ground, into storm sewers or bodies of water.

Methods for cleaning up: Prevent further leakage or spillage if safe to do so. Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see Section 13).

7. HANDLING AND STORAGE

Advice on safe handling:	Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly after handling.
Storage Conditions:	Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children. Keep from freezing.
Incompatible materials	Incompatible with oxidizing agents. Strong acids.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Occupational Exposure Limits:

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
Butoxyethanol 111-76-2	TWA: 20 ppm	TWA: 50 ppm TWA: 240 mg/m ³ (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m ³ (vacated) Sk* Sk*	IDLH: 700 ppm TWA: 5 ppm TWA: 24 mg/m ³
Hydrochloric Acid 7647-01-0	Ceiling: 2 ppm	(vacated) Ceiling: 5 ppm (vacated) Ceiling: 7 mg/m ³ Ceiling: 5 ppm Ceiling: 7 mg/m ³	IDLH: 50 ppm Ceiling: 5 ppm Ceiling: 7 mg/m ³

Engineering Controls:	Provide good general ventilation. If work practices generate dust, fumes, gas, vapors or mists which expose workers to chemicals above the occupational exposure limits, local exhaust ventilation or other engineering controls should be considered.
------------------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Individual protection measures, such as personal protective equipment

Eye/face protection:	Wear splash goggles.
Skin and body protection:	Wear rubber or other chemical-resistant gloves.
Respiratory protection:	Not required with expected use. If occupational exposure limits are exceeded or respiratory irritation occurs, use of a NIOSH/MSHA approved respirator suitable for the use-conditions and chemicals in Section 3 should be considered.
General hygiene considerations:	Wash hands and any exposed skin thoroughly after handling. See 29 CFR 1910.132-138 for further guidance.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state:	Liquid
Color:	Light green
Odor:	Floral fragrance
Odor Threshold:	No information available

Property	Values	Remarks • Method
pH:	11.2-11.8	
Melting Point / Freezing Point:	No data available	
Boiling Point / Boiling Range:	100 °C / 212 °F	
Flash Point:	> 100 °C / 212 °F	ASTM D56
Evaporation Rate:	< 1	(Butyl acetate = 1)
Flammability (solid, gas):	No data available	No information available
Flammability Limits in Air:		No information available
Upper Flammability Limit:	No data available	
Lower Flammability Limit:	No data available	
Vapor Pressure:	No data available	No information available
Vapor Density:	No data available	No information available
Relative Density:	1.048	
Solubility(ies):	Soluble in water	
Partition Coefficient:	No data available	No information available

Autoignition Temperature:	Not applicable	
Decomposition Temperature:	Not applicable	
Kinematic Viscosity:	No information available	No information available
Particle characteristics:	Not applicable	

10. STABILITY AND REACTIVITY

Reactivity:	This material is considered to be non-reactive under normal conditions of use.
Chemical stability:	Stable under normal conditions.
Possibility of hazardous reactions:	Not expected to occur with normal handling and storage.
Conditions to Avoid:	Extremes of temperature and direct sunlight
Incompatible materials:	Strong oxidizing agents. Strong acids.
Hazardous decomposition products:	May include carbon monoxide, carbon dioxide (CO ₂) and other toxic gases or vapors.

11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure:	Eyes, Skin, Ingestion, Inhalation.
Symptoms of Exposure:	
Eye contact:	Pain, redness, swelling of the conjunctiva and tissue damage. Eye contact may cause permanent damage.
Skin contact:	Pain, redness, blistering and possible chemical burn.
Inhalation:	Irritation or damage to the mucus membranes of the respiratory tract. Nasal discomfort and coughing.
Ingestion:	Damage or chemical burns to mouth, throat and stomach. Pain, nausea, vomiting and diarrhea.

Immediate, Delayed, Chronic Effects

Product Information:	Data not available or insufficient for classification.
Target organ effects:	Blood. Central nervous system. Eyes. hematopoietic system. Kidney. Liver. Respiratory system. Skin.

Acute toxicity

Numerical measures of toxicity:

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	12,558.70 mg/kg
ATEmix (dermal)	30,095.50 mg/kg
ATEmix (inhalation-vapor)	108.4971 mg/l
ATEmix (inhalation-dust/mist)	25.30 mg/l

Component Information:

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Water 7732-18-5	> 90 mL/kg (Rat)	-	-
C9-11 Alcohols Ethoxylated 68439-46-3	= 1400 mg/kg (Rat)	-	-
Sodium Carbonate 497-19-8	= 4090 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	= 2300 mg/m ³ (Rat) 2 h
Butoxyethanol 111-76-2	= 470 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	= 450 ppm (Rat) 4 h = 486 ppm (Rat) 4 h
Tetrasodium EDTA 64-02-8	= 1658 mg/kg (Rat)	-	-
Hydrochloric Acid 7647-01-0	238 - 277 mg/kg (Rat)	> 5010 mg/kg (Rabbit)	= 1.68 mg/L (Rat) 1 h
Benzyl Benzoate 120-51-4	> 2000 mg/kg (Rat)	= 4000 mg/kg (Rabbit)	-
Acid Green 25 4403-90-1	> 10 g/kg (Rat)	-	-
Acid Yellow 36 587-98-4	= 5000 mg/kg (Rat)	-	-

Carcinogenicity: No components present at 0.1% or greater are listed as to being carcinogens by ACGIH, IARC, NTP or OSHA.

12. ECOLOGICAL INFORMATION

Ecotoxicity:

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Sodium Carbonate 497-19-8	-	LC50: =300mg/L (96h, Lepomis macrochirus) LC50: 310 - 1220mg/L (96h, Pimephales promelas)	-	EC50: =265mg/L (48h, Daphnia magna)
Butoxyethanol 111-76-2	-	LC50: =1490mg/L (96h, Lepomis macrochirus) LC50: =2950mg/L (96h, Lepomis macrochirus)	-	EC50: >1000mg/L (48h, Daphnia magna)
Tetrasodium EDTA 64-02-8	-	LC50: =41mg/L (96h, Lepomis macrochirus) LC50: =59.8mg/L (96h, Pimephales promelas)	-	-
Benzyl Benzoate 120-51-4	-	LC50: =2.32mg/L (96h, Danio rerio)	-	-

Persistence and Degradability: No information available.

Bioaccumulation: No information available.

Mobility in Soil: No information available

Other adverse effects: No information available.

13. DISPOSAL CONSIDERATIONS

Waste from residues/unused products: Dispose of in accordance with federal, state and local regulations.

Contaminated packaging: Dispose of in accordance with federal, state and local regulations.

14. TRANSPORT INFORMATION

UN/ID No: UN1760
Proper Shipping Name: Corrosive liquids, n.o.s., (contains sodium hydroxide)
Hazard Class: 8
Packing Group: III
Special Provisions: Shipping descriptions may vary based on mode of transport, quantities, package size, and/or origin and destination. Check with a trained hazardous materials transportation expert for information specific to your situation.

IMDG:

UN number or ID number: UN1760
Proper Shipping Name: Corrosive liquids, n.o.s., (contains sodium hydroxide)
Hazard Class: 8
Packing Group: III

15. REGULATORY INFORMATION

TSCA (Toxic Substance Control Act Section 8(b) Inventory)

All chemical substances in this product are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

SARA 313

This product does not contain listed substances above the "de minimus" level

Butoxyethanol - 111-76-2

applies to R-(OCH₂CH₂)_n-OR', where n = 1, 2, or 3, R=Alkyl C7 or less, or R = Phenyl or Alkyl substituted phenyl, R' = H or Alkyl C7 or less, or OR' consisting of Carboxylic acid ester, Sulfate, Phosphate, Nitrate, or Sulfonate Chemical Category N230

SARA 311/312 Hazard Categories

Acute health hazard:	Yes
Chronic Health Hazard:	No
Fire hazard:	No
Sudden release of pressure hazard:	No
Reactive Hazard:	No

California Proposition 65

This product is not subject to warning requirements under California Proposition 65.

16. OTHER INFORMATION

NFPA	Health hazards: 3	Flammability: 0	Instability: 0	Special hazards: -
HMIS	Health hazards: 3	Flammability: 0	Physical hazards: 0	

Revision Date: 14-Apr-2025
Revision Note: Section, 2, 3, 7, 9, 11, 12

Disclaimer:

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet