

MATERIAL SAFETY DATA SHEET: LIQUA-SEAL

Section I - General Information

(000000-000000- - 0398)

Date of Issue:

1/21/1997 12:00:00 AM

Supersedes:

4/26/1996 12:00:00 AM

Chemical Name & Synonyms:

N/A

Trade Name & Synonyms:

LIQUA-SEAL

Chemical Family:

ASPHALTIC EMULSION

Formula is a mixture: [v]

Manufacturer Name:

CERTIFIED LABS, DIV. OF NCH CORP.

Manufacturer Address:

BOX 152170
IRVING, TEXAS 75015

Prepared By:

L ASKEW/CHEMIST

Product Code Number:

0398

Emergency Phone Number:

800-424-9300

Section II - Hazardous Ingredients

THE HAZARDS PRESENTED BELOW ARE THOSE OF THE INDIVIDUAL COMPONENTS

Chemical Name (Ingredients)

ASPHALT

Hazard

IRRITANT

TLV

5MG/M3 1.

PEL

5MG/M3 2.

STEL

NOT EST.

CAS #

8052-42-4

Section IIa - Non-Hazardous Ingredients

(NON-HAZARDOUS INGREDIENT NAMES AND CAS NUMBERS ARE PROTECTED UNDER NJ TRADE)

Secret Registry #: 409363- 5195P

Section III - Physical Data

Boiling Point (?F): 212 IBP

Specific Gravity (H₂O=1): 1.1

Vapor Pressure (mm Hg): 18MM@25C

Color: BLACK

Vapor Density (Air=1): >1

Odor: ASPHALTIC

pH @ 100% : 7-9

Clarity: OPAQUE

% Volatile by Volume: 40-60

Evaporation Rate (BuAc=1): <1

H₂O Solubility: APPRECIABLE

Viscosity: VISCOUS

Section IV - Fire and Explosion Hazard

Flash Point: NON-FLAM

Method Used: T.C.C.

Flammable Limits: N/E

UEL: N/E

LEL: N/E

Aerosol Level (NFPA 30B): N/A

Extinguishing Media:

[v] Foam	[v] Alcohol Foam	[v] CO2
[v] Dry Chemical	[v] Water Spray	[v] Other

NFPA 704 Hazard Rating:

4-Extreme	Health: 1
3-High	Flammability: 1
2-Moderate	Instability: 0
1-Slight	Special:
0-Insignificant	

Special Fire Fighting Procedures:

MATERIAL SAFETY DATA SHEET: LIQUA-SEAL

FIREFIGHTERS SHOULD WEAR A SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE GEAR. EXTINGUISHING MEDIA SHOULD BE CHOSEN BASED ON THE NATURE OF THE SURROUNDING FIRE.

Unusual Fire and Explosion Hazards:
NONE KNOWN.

Section V - Health and Hazard Data

Threshold Limit Value:

NOT ESTABLISHED FOR MIXTURE. SEE SECTION II.

Effects of Overexposure:

Acute: (Short Term Exposure)

EYE CONTACT: MAY CAUSE IRRITATION SEEN AS ITCHING AND REDNESS. INGESTION: MAY CAUSE GASTROINTESTINAL IRRITATION SEEN AS NAUSEA, VOMITING AND DIARRHEA. INHALATION: MAY CAUSE IRRITATION SEEN AS COUGHING AND SNEEZING. SKIN CONTACT: MAY CAUSE IRRITATION SEEN AS ITCHING AND REDNESS.

Chronic: (Long Term Exposure)

NO CHRONIC DATA AVAILABLE. TARGET ORGANS: NONE KNOWN. ALTHOUGH THERE IS NO PRIMARY ROUTE OF ENTRY INTO THE BODY, THE PRIMARY ROUTE OF EXPOSURE IS SKIN AND EYE CONTACT. MEDICAL CONDITIONS AGGRAVATED: NONE KNOWN.

Primary Routes of Entry

☐ Inhalation ☐ Ingestion ☐ Absorption

Emergency First Aid Procedures:

Inhalation:

REMOVE FROM THE AREA TO FRESH AIR. SEEK MEDICAL ATTENTION IF RESPIRATORY IRRITATION DEVELOPS OR IF BREATHING BECOMES DIFFICULT.

Eye Contact:

RINSE THE EYES WITH WATER. REMOVE ANY CONTACT LENSES AND CONTINUE FLUSHING WITH PLENTY OF WATER FOR SEVERAL MINUTES. SEEK MEDICAL ATTENTION IF IRRITATION DEVELOPS.

Skin Contact:

WASH AFFECTED AREAS WITH PLENTY OF SOAP AND WATER FOR SEVERAL MINUTES. SEEK MEDICAL ATTENTION IF IRRITATION DEVELOPS.

Ingestion:

GIVE 3 TO 4 GLASSES OF WATER, BUT DO NOT INDUCE VOMITING. IF VOMITING OCCURS, GIVE FLUIDS AGAIN. SEEK MEDICAL ATTENTION IF DISCOMFORT OCCURS.

Notes to Physician:

ALTHOUGH THERE IS NO SPECIFIC ANTIDOTE, TREAT THE PATIENT SYMPTOMATICALLY.

Section VI - Toxicity Information

Product Contains Chemicals Listed as Carcinogen or Potential Carcinogen By:

☐ IARC ☐ NTP ☐ OSHA ☐ ACGIH ☐ Other

ASPHALT
NO DATA AVAILABLE.

Section VII - Reactivity Data

Stability

☒ Stable ☐ Unstable

Conditions to Avoid:

AVOID HEAT, HOT SURFACES, SPARKS AND OPEN FLAMES.

Hazardous Polymerization

☒ Will not occur ☐ May occur

Conditions to Avoid:

N/A

Incompatibility (Materials to Avoid):

OXIDIZING AGENTS, REDUCING AGENTS, ACIDS AND BASES.

Hazardous Decomposition Products:

OXIDES OF CARBON.

Section VIII - Spill Or Leak Procedures

MATERIAL SAFETY DATA SHEET: LIQUA-SEAL

Steps to be Taken if Material is Released or Spilled:

PREVENT PRODUCT FROM CONTAMINATING SOIL OR FROM ENTERING SEWAGE AND DRAINAGE SYSTEMS AND BODIES OF WATER. DIKE AND CONTAIN SPILL IF SAFE TO DO SO. ABSORB WITH AN INERT MATERIAL AND TRANSFER ALL MATERIAL INTO A PROPERLY LABELED CONTAINER FOR DISPOSAL. RECOVER FREE LIQUID AND RETURN TO CONTAINER. WEAR APPROPRIATE PROTECTIVE CLOTHING.

Waste Disposal Method(s):

DISPOSE OF IN ACCORDANCE WITH ALL FEDERAL, STATE, AND LOCAL REGULATIONS.

Neutralizing Agent:

N/A

Section IX - Special Protection Information

Required Ventilation:

GENERAL VENTILATION IS NORMALLY ADEQUATE.

Respiratory Protection:

NONE REQUIRED UNDER NORMAL CONDITIONS OF USE.

Glove Protection:

NEOPRENE RUBBER OR NITRILE GLOVES IF REPEATED OR PROLONGED SKIN CONTACT IS LIKELY.

Eye Protection:

SAFETY GLASSES IF THE METHOD OF USE PRESENTS THE LIKELIHOOD OF EYE CONTACT.

Other Protection:

WEAR PROTECTIVE CLOTHING WHEN HANDLING.

Section X - Storage and Handling Information

Storage Temperature

Max: 100 F. Min: 35 F.

Storage Conditions

☒ Indoors ☐ Outdoors ☐ Heated ☐ Refrigerated

Precautions to be Taken in Handling and Storing:

ALWAYS STORE MATERIAL IN ITS ORIGINAL CONTAINER. KEEP CONTAINER TIGHTLY CLOSED WHEN NOT IN USE. KEEP FROM FREEZING. IF PRODUCT FREEZES ALLOW IT TO SLOWLY WARM TO ROOM TEMPERATURE AND STIR THOROUGHLY BEFORE USING.

Other Precautions:

KEEP OUT OF REACH OF CHILDREN. READ THE ENTIRE LABEL BEFORE USING THE PRODUCT. FOLLOW THE LABEL DIRECTIONS.

Section XI - Regulatory Information

Chemical Name

None.

CAS Number**Upper % Limit**

Those Ingredients listed above are subject to the reporting requirements of 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR part 372.

Please call 1-800-527-9919 for additional information if you are a California customer. This MSDS is not intended for users in the state of California.

Section XII - References

1. THRESHOLD LIMIT VALUES FOR CHEMICAL SUBSTANCES AND PHYSICAL AGENTS AND BIOLOGICAL EXPOSURE INDICES, ACGIH, 1995-1996.
 2. OSHA PEL.
 3. VENDOR'S MSDS.
- IRR:IRRITANT, FLAM/FLAMM:FLAMMABLE, COMB:COMBUSTIBLE, CORR:CORROSIVE, CARC:CARCINOGENIC, TOX:TOXIC, N/A:NOT APPLICABLE, N/E:NOT ESTABLISHED, COC:CLEVELAND OPEN CUP, PMCC:PENSKY-MARTIN CLOSED CUP, TCC:TAGLIABUE CLOSED CUP, LEL:LOWER EXPLOSION LIMIT, UEL:UPPER EXPLOSION LIMIT, NFPA:NATIONAL FIRE PROTECTION ASSOCIATION, IARC:INTERNATIONAL AGENCY FOR THE RESEARCH ON CANCER, NTP:NATIONAL TOXICOLOGY PROGRAM, OSHA:OCCUPATIONAL SAFETY & HEALTH ADMINISTRATION, ACGIH:AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS, TLV:THRESHOLD LIMIT VALUE, PEL:PERMISSIBLE EXPOSURE LEVEL, STEL:SHORT TERM EXPOSURE LIMIT, MLD:MILD, MOD:MODERATE, SEV:SEVERE,

MATERIAL SAFETY DATA SHEET: LIQUA-SEAL

MUT:MUTAGENIC, ASPHYX:ASPHYXIAN

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE IN LIGHT OF CURRENT FORMULATION. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THE DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF.

CERTIFIED LABS, DIV. OF NCH CORP. assumes no responsibility for personal injury or property damage caused by the use, storage, or disposal of the product in a manner not recommended on the product label. Users assume all risks associated with such unrecommended use, storage, or disposal of the product.

©2008 [NCH Corporation](#) All rights reserved.